



ITERCOLD | COLD MIX FOR ROAD MAINTENANCE

1. APPLICATION

ITERCOLD has the following properties:

- Is a plastic sacked mix, ready to use, to fill-in road surface potholes, especially during winter time, caused by rain and frost.
- Has the capacity to restore small surfaces where digging has been realized for electric, phone or plumbing conduct laying.
- Is easy to apply and remains plastic during summer or winter time. It can be applied on humid or wet surfaces, because it contains a suitable antistripping agent which guarantees a perfect seal.
- After the application, the traffic will guarantee the perfect compacting without the product coming out of the pothole, previously cleaning the surface to be treated using a suitable primer and a minimum compacting of the product.

2. DOSAGE

ITERCOLD has an approximate specific weight of 1500 Kg/m^3 which corresponds to about 15 Kg of product for each square meter and each 1 cm thickness of the hole.

3. COMPOSITION

Aggregates, bitumen, antistripping agents and specific plasticizer.

4. PHYSICAL PROPERTIES

Aspect	plastic granulates
Approximate Density	1500 Kg/m^3
Plasticizer Additive	not less than 25% by bitumen weight

Innovative chemistry for road paving | www.iterchimica.com

The herein information are based on our current knowledge and experience. It may not, under any circumstances, imply warranty on our part, nor liability for the use of our products, not being the condition of the employment under our control.



5. STORAGE

Sheltered from weather conditions.

6. PACKAGE

In bag of 30Kg net weight.

7. SAFETY PRECAUTIONS

See the product's safety instruction sheet.

REV 01-2010

Innovative chemistry for road paving | www.iterchimica.com